

# Comfort-Cire®

## SE Series

**80 - 96% AFUE  
GAS FURNACES**

Single Stage  
Two Stage



HEAT  CONTROLLER



## 80 % AFUE GAS FURNACES

### GFM80S FEATURES

- Durable aluminized steel tubular heat exchanger
- Hot-surface ignition for dependable operation
- Quiet multi-speed ECM blower
- Designed for multi-position installation: Upflow, Downflow, Horizontal
- Natural gas and propane (LP) convertible, LP kit included
- Industry-standard cabinet sizes for easy replacement, installation and add-on cooling
- Convenient left or right connection for gas and electric service
- Removable base for side or bottom return application



### GFM80S SPECS AT A GLANCE

Model	AFUE	BTU Input	Configuration	Dimensions (in.) (H x W x D)
GFM80S040A3S1A	80%	40,000	Upflow/Downflow/Horizontal	24-15/16 x 23-5/8 x 23-5/8
GFM80S060A3S1A	80%	60,000	Upflow/Downflow/Horizontal	24-15/16 x 23-5/8 x 23-5/8
GFM80S060B4S1A	80%	60,000	Upflow/Downflow/Horizontal	24-15/16 x 28 x 28
GFM80S080B4S1A	80%	80,000	Upflow/Downflow/Horizontal	24-15/16 x 29-1/8 x 29-1/8
GFM80S080C4S1A	80%	80,000	Upflow/Downflow/Horizontal	33-3/16 x 28 x 28
GFM80S100C5S1A	80%	100,000	Upflow/Downflow/Horizontal	33-3/16 x 28 x 28
GFM80S120D5S1A	80%	100,000	Upflow/Downflow/Horizontal	33-3/16 x 29-1/8 x 29-1/8





## 96 % AFUE GAS FURNACES

### GFM96T FEATURES

- Durable aluminized steel tubular heat exchanger
- Stainless-steel secondary heat exchanger
- Two-stage gas valve
- Hot surface ignition for dependable operation
- Quiet multi-speed ECM blower motor
- Control board with self-diagnostics and low-voltage terminal block
- Natural gas and propane (LP) convertible
- Designed for multi-position installation: Upflow and Horizontal
- Industry-standard cabinet sizes for easy replacement, installation and add-on cooling
- Convenient left or right connection for gas and electric service
- Removable base for side or bottom return applications



### GFM96T SPECS AT A GLANCE

Model	AFUE	BTU Input	Configuration	Dimensions (in.) (H x W x D)
GFM96T060B3S1A	96%	60,000	Upflow/Horizontal	34-1/2 x 17-1/2 x 28-1/2
GFM96T080B3S1A	96%	80,000	Upflow/Horizontal	34-1/2 x 17-1/2 x 28-1/2
GFM96T080C4S1A	96%	80,000	Upflow/Horizontal	34-1/2 x 21 x 28-1/2
GFM96T100C5S1A	96%	100,000	Upflow/Horizontal	34-1/2 x 21 x 28-1/2
GFM96T100D5S1A	96%	100,000	Upflow/Horizontal	34-1/2 x 24-1/2 x 28-1/2
GFM96T120D5S1A	96%	120,000	Upflow/Horizontal	34-1/2 x 24-1/2 x 28-1/2





### COME HOME TO COMFORT. COME HOME TO COMFORT-AIRE®

When you think about everything Comfort-Aire® delivers, your decision is easy. With Comfort-Aire®, all your heating and cooling questions are answered. The performance and reliability you want are right here, and ready to go to work.

**Comfort-Aire®. It's the right choice.**

#### California Only

This furnace does not meet the South Coast Air Quality Management District (SCAQMD) Rule 1111 and San Joaquin Valley Air Pollution Control District (SJVAPCD) Rule 4905 NOx emission limit (14 ng/J) and cannot be installed within the SCAQMD or SJVAPCD and Bay Area.



"This product complies with all California product labeling laws including, but not limited to, the Safe Drinking Water and Toxic Enforcement Act of 1986, more commonly known as Proposition 65."

Due to ongoing product improvements, specifications and dimensions are subject to change and correction without notice or incurring obligations. Determining the application and suitability for use of any product is the responsibility of the installer. Additionally, the installer is responsible for verifying dimensional data on the actual product prior to beginning any installation preparations.

Third party incentive and rebate programs have precise requirements as to product performance and certification. All products meet applicable regulations in effect on date of manufacture; however, certifications are not necessarily granted for the life of a product. Therefore, it is the responsibility of the applicant to determine whether a specific model qualifies for these incentive/rebate programs.