

CONSTANT TORQUE AIR HANDLERS

AMC FEATURES

- Available for cooling and heat pump applications
- Multi-speed ECM blower motor
- Factory-sealed cabinet certified to achieve 2% or less leakage rate at 1.0 inch water column
- Multi-position installation
- Horizontal and vertical condensate drain pans standard
- Blower and coil slide out for ease of maintenance
- Field installed heater kits are optional: 5/7.5/10/15/20kW
- AHRI Listed & ETL Certified



AMC SPECS AT A GLANCE

Model	Voltage	Hertz	HP	Speeds	Circuit Amps	Max Circuit Protector	Dimensions (in.) (H x W x D)
AMC24S1A	208/230	60	1/3	5	2.6	15(A)	41-3/8 x 18-1/8 x 20-1/2
AMC36S1A	208/230	60	1/2	5	3.0	15(A)	46-1/2 x 19-5/8 x 21-5/8
AMC60S1A	208/230	60	3/4	5	4.5	15(A)	54-1/2 x 22 x 24



PSC AIR HANDLERS

AMP FEATURES

- Available for cooling and heat pump applications
- All aluminum tubes & fins
- Factory-sealed cabinet certified to achieve 2% or less leakage rate at 1.0 inch water column
- Multi-position installation
- Horizontal and vertical condensate drain pans standard
- Blower and coil slide out for ease of maintenance
- Field installed heater kits are optional: 5/7.5/10/15/20kW
- AHRI Listed & ETL Certified



AMP SPECS AT A GLANCE

Model	Voltage	Hertz	HP	Speeds	Circuit Amps	Max Circuit Protector	Dimensions (in.) (H x W x D)
AMP24S1A	208/230	60	1/5	3	2.6	15(A)	46-1/2 x 19-5/8 x 21-5/8
AMP36S1A	208/230	60	1/3	3	3.2	15(A)	46-1/2 x 19-5/8 x 21-5/8
AMP48S1A	208/230	60	1/2	3	4.3	15(A)	54-1/2 x 22 x 24
AMP60S1A	208/230	60	3/4	3	4.4	15(A)	54-1/2 x 22 x 24