

HEAT PUMPS


RSH15 FEATURES

- R410A chlorine-free refrigerant
- Energy-efficient compressor
- Internal protection against high temperature motoroverload conditions
- High quality condenser with inner-groove copper tube and aluminum fin
- AHRI Listed & ETL Certified
- 45° Service valves with sweat connections and easy-access gauge ports
- Factory-installed high pressure switch and low pressure switch
- Filter drier included



RSH SPECS AT A GLANCE

Model	Compressor	Tonnage	Sound Power (dB)	Dimensions (in.) (H x W x D)
RSH1518S1A	Scroll	1.5	72	24-15/16 x 23-5/8 x 23-5/8
RSH1524S1A	Scroll	2.0	74	24-15/16 x 28 x 28
RSH1530S1A	Scroll	2.5	73	24-15/16 x 28 x 28
RSH1536S1A	Scroll	3.0	73	24-15/16 x 28 x 28
RSH1542S1A	Scroll	3.5	76	33-3/16 x 29-1/8 x 29-1/8
RSH1548S1A	Scroll	4.0	76	33-3/16 x 29-1/8 x 29-1/8
RSH1560S1A	Scroll	5.0	78	33-3/16 x 29-1/8 x 29-1/8



**Come Home to Comfort.
Come Home to *Century*.**



SE Series

Due to ongoing product improvements, specifications and dimensions are subject to change and correction without notice or incurring obligations. Determining the application and suitability for use of any product is the responsibility of the installer. Additionally, the installer is responsible for verifying dimensional data on the actual product prior to beginning any installation preparations.

Third party incentive and rebate programs have precise requirements as to product performance and certification. All products meet applicable regulations in effect on date of manufacture; however, certifications are not necessarily granted for the life of a product. Therefore, it is the responsibility of the applicant to determine whether a specific model qualifies for these incentive/rebate programs.

"This product complies with all California product labeling laws including, but not limited to, the Safe Drinking Water and Toxic Enforcement Act of 1986, more commonly known as Proposition 65."